



# Medium-duty 1-3/8" Insulated Sectional Door

Amarr® 2731





## Solid commercial construction meets variety and style.

The Amarr 2731 is built with two 27-gauge steel skins surrounding 1-3/8" HFC-free polystyrene. The multi-step insulation system includes tongue and groove construction, HFC-free polystyrene insulation and weather stripping that provides a solid wall of protection against the elements.


The exterior steel skin features a flush profile with woodgrain embossment for a more upscale look reminiscent of typical residential doors. The interior skin features a flush profile with stucco embossment for a clean interior surface.



### CONSTRUCTION

**R-Value 6.7** Amarr 2731  
Medium-duty, 1-3/8" 27-gauge steel

#### TRIPLE-LAYER Steel + Insulation + Steel



**Track:** All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit [www.amarr.com](http://www.amarr.com).

**Springs:** Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

**Standard Hardware:** Galvanized steel hinges and track brackets. All rollers have minimum 10-ball bearings.

### SPECIFICATIONS

	Medium-duty <b>Amarr 2731</b>
EXTERIOR STEEL THICKNESS	27 ga
PANEL DESIGN	Flush
STEEL EMBOSSMENT	Woodgrain
DOOR THICKNESS	1-3/8" [3.5cm]
CONSTRUCTION LAYERS	Triple
INSULATION <sup>1</sup>	Polystyrene
R-VALUE <sup>2</sup>	6.7
MINIMUM WIDTH	6'
MAXIMUM WIDTH	18' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	14' 1"
WIND LOAD <sup>3</sup> AVAILABLE	•
PAINT FINISH WARRANTY <sup>4</sup>	10 Years
WORKMANSHIP/HARDWARE WARRANTY <sup>4</sup>	1 Year

<sup>1</sup> Insulation has passed self-ignition, flamespread and smoke developed index fire testing. <sup>2</sup> Calculated door section R-value is in accordance with DASMA TDS-163. <sup>3</sup> It is your responsibility to make sure your garage door meets local building codes. <sup>4</sup> For complete warranty details, visit [amarr.com](http://amarr.com) or contact your local Amarr dealer.



Rapid Install Vertical Lift: Designed specifically for commercial warehouse and dock doors and saves approximately 20 minutes of installation time per door due to fewer jamb attachments and a pre-assembled, one-piece track. Available for door sizes up to 9'4"x10'. For more information, please visit [www.amarr.com](http://www.amarr.com).

### WINDOW OPTIONS



21" x 13" SHORT PANEL\*



24" X 6" DOUBLE INSULATED ACRYLIC\*\*



41" x 13" LONG PANEL\*

\*True White shown; also available in Almond, Wicker Tan, and Sandtone. Available with Clear, Obscure, or Insulated glass.  
\*\*Available with black frame only.

### PANEL




FLUSH PANEL WITH WOODGRAIN EMBOSSMENT

### COLORS

Actual paint colors may vary from samples shown.



TRUE WHITE (TW)



ALMOND (AL)



SANTONE (ST)



**Amarr Color Zone<sup>1</sup>**  
Over 800 SnapDry™ paint colors. Approved list can be found at [amarr.com/amarr\\_color\\_zone](http://amarr.com/amarr_color_zone). Your local Sherwin-Williams store can provide SnapDry™ paint chips.



WICKER TAN (WK)

Amarr steel doors are pre-painted; owners can use exterior latex paint for custom colors. Visit [amarr.com](http://amarr.com) for painting instructions. Painting your door voids the warranty.

**Entrematic**  
165 Carriage Court  
Winston-Salem, NC 27105  
800.503.DOOR  
[www.amarr.com](http://www.amarr.com)



YOUR LOCAL AMARR DEALER: